



Tool Comparison Chart



Electric Models

Model	Clearing Area	Power Supply	Horsepower	Weight (lbs)	Removal Rate (Sq. ft. per hour)
K7-1	5" Wide	115V	¼	9	50-75
K7-2	5" Wide	230V	¼	9	50-75
K7-1E	8" Wide	115V	¼	11	65-90
K7-2E	8" Wide	230V	¼	11	65-90
M5-1	8" Wide	115V	½	21	70-100
M5-2	8" Wide	230V	½	21	70-100
M5-1E	12" Wide	115V	½	27	100-150
M5-2E	12" Wide	230V	½	27	100-150
W1E	5" Wide	115V	2	97	250-350

Pneumatic Models

Model	Clearing Area	Power Supply	Horsepower	Weight (lbs)	Removal Rate (Sq. ft. per hour)
KP5	5" Wide	42CFM/	70-100 PSI	¾	6 50-75
KP5E	8" Wide	42CFM/	70-100 PSI	¾	8 65-90
MP6	8" Wide	42CFM/	70-100 PSI	2.5	17 70-100
MP6E	12" Wide	42CFM/	70-100 PSI	2.5	23 100-150

Gas Models

Model	Clearing Area	Power Supply	Horsepower	Weight (lbs)	Removal Rate (Sq. ft. per hour)
W1G	5" Wide	Gas	5	92	250-350

Serving the world with quality surface preparation tools since 1937!